
Part Number: M2450DLCB

Airgain))





Ultra 35DB Antenna


High gain, case mounted embedded antenna for easy integration


The Ultra 35DB Embedded Antenna provides a high efficiency, dual band, embedded antenna solution for Wi-Fi and ISM applications in the 2.4 GHz and 5 GHz bands. As efficient embedded antenna solutions become the focus of next generation wireless product design, the Ultra35DB antenna provides the combination of small size with top performance. This antenna was designed to accommodate most WLAN applications, such as access points, routers, and gateways. The Ultra35DB, optimized for mounting in a plastic case, can be easily integrated into an ID design.


ANTENNA RADIATION PATTERNS











Airgain USA sales@airgain.com 1930 Palomar Point Way, Suite 107 Carlsbad, CA 92008 +1 760 579 0200

Airgain Taiwan asiasales@airgain.com 7F, No. 506, Syecian Road Shulin City, Taipei County 23853 Taiwan, R.O.C. +2 2929 4460

FEATURES

- > 802.11 a/b/g/n standard
- > Case mounting
- > 4 dBi peak gain

BENEFITS

- > Eliminates external dipole
- > Enables quick integration
- > Achieves high performance


Expanding the Range of Wireless Possibilities

Ultra 35DB Antenna

Airgain*)))

PRODUCT SPECIFICATIONS	
Standard	IEEE 802.11n and 802.11 a/b/g
Frequency Band	2.4 to 2.49 GHz, 4.9 to 5.9GHz
Peak Gain	3.5 dBi @2.44GHz, 4.0 dBi @ 5.2 GHz, 4.0 dBi @5.8 GHz
VSWR	2:1 Max
Feed Impedance	50 Ohms
Power Handling	30 dBm
Interface	50 ohm, 1.13mm diameter, micro coax cable, U.FL compatible cable connector (optional) Cable mounted EMI ferrites (optional)
Dimensions	35.8 x 8.5 x 7.7 (mm)
Weight	1.7 g (0.06 oz)


MECHANICAL DIMENSIONS




Detail 1 shows correct cable soldering
Detail 2 shows correct cable and connector orientation

Figure 5a

Model M2450DLCB Dimensions
Unless otherwise specified, dimension tolerances are +/- 0.1 mm



Model M2450DLCB-T: Pre-applied Tape Dimensions



Model M2450DLCB Footprint Unless otherwise specified, dimension tolerances are +/- 0.1 mm

Information in this document is provided in connection with Airgain™ products. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in Airgain's Terms and Conditions of Sale for such products, Airgain assumes no liability whatsoever, and Airgain disclaims any express or implied warranty, relating to sale and/or use of Airgain products including liability or warranties relating to fitness or a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Airgain may make changes to specifications and product descriptions at any time, without notice. for the most current product information, please visit: www.airgain.com

 $Copyright @2009. Airgain, Inc. All \ rights \ reserved. Airgain \ and \ the \ Airgain \ logo \ are \ trademarks \ of \ Airgain, Inc. \ DS/Ult35DB/1209$